

# TIGER G2



TG-T12-20

|                                   |  |
|-----------------------------------|--|
| <b>Article no.</b>                | TG-T12-20                                |
| <b>Frequency</b>                  | 433 MHz , 69 channels                    |
| <b>Duplex</b>                     | Yes                                      |
| <b>Mod.type</b>                   | FM-modulation                            |
| <b>Radio type</b>                 | -  |
| <b>Buttons</b>                    | 4 x 1 -step buttons                      |
| <b>No. of batteries</b>           | 1  |
| <b>Battery</b>                    | Re-chargeable & exchangeable             |
| <b>Type of batteries</b>          | li-ion                                   |
| <b>Weight</b>                     | 1200 g /~ 2.6 lb                         |
| <b>Dimensions</b>                 | 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 In |
| <b>Protection</b>                 | IP65                                     |
| <b>Temperature</b>                | -20 to +55 °C / -4 to 131 F              |
| <b>Safety level</b>               | PLe, SIL3                                |
| <b>Certifications</b>             | CE, G Lloyd                              |
| <b>On/off switch</b>              | No                                       |
| <b>RFID</b>                       | Accessory: wall tag                      |
| <b>PIN code</b>                   | 10                                       |
| <b>Joystick directions:</b>       | 2x2 + 0x2                                |
| <b>RF-power output:</b>           | 10mW (by 50 ohm)                         |
| <b>Op. time with cont. usage:</b> | 16 h                                     |

The product picture above is for illustrative purposes only, actual product appearance might be slightly different