

TIGER 62



TG-T12-22

Frequency 433 MHz , 69 channels Duplex Yes Mod.type FM-modulation Radio type - Buttons 4 x 1 -step buttons No. of batteries 1 Battery Re-chargeable & exchangeable Type of batteries Ii-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10 mW (by 50 ohm)		
Duplex Yes Mod.type FM-modulation Radio type - Buttons 4 x 1 -step buttons No. of batteries 1 Battery Re-chargeable & exchangeable Type of batteries li-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Article no.	TG-T12-22
FM-modulation Radio type Buttons 4 x 1 - step buttons No. of batteries 1 Battery Re-chargeable & exchangeable Type of batteries li-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Frequency	433 MHz , 69 channels
Radio type Buttons 4 x 1 -step buttons No. of batteries 1 Battery Re-chargeable & exchangeable Type of batteries li-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Duplex	Yes
Buttons 4 x 1 -step buttons No. of batteries 1 Battery Re-chargeable & exchangeable Type of batteries II-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Mod.type	FM-modulation
No. of batteries Battery Re-chargeable & exchangeable Type of batteries li-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Radio type	-
Re-chargeable & exchangeable Type of batteries Ili-ion Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Buttons	4 x 1 -step buttons
Ii-ion	No. of batteries	1
Weight 1200 g /~ 2.6 lb Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Battery	Re-chargeable & exchangeable
Dimensions 210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Type of batteries	li-ion
Protection IP65 Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Weight	1200 g /~ 2.6 lb
Temperature -20 to +55 °C / -4 to 131 F Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Dimensions	210 x 140 x 130 mm /~ 8.3 x 5.5 x 5.1 ln
Safety level PLe, SIL3 Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Protection	IP65
Certifications G Lloyd, CE On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Temperature	-20 to +55 °C / -4 to 131 F
On/off switch No RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Safety level	PLe, SIL3
RFID Accessory: wall tag PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	Certifications	G Lloyd, CE
PIN code 10 Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	On/off switch	No
Joystick directions: 4x4 + 0x4 RF-power output: 10mW (by 50 ohm)	RFID	Accessory: wall tag
RF-power output: 10mW (by 50 ohm)	PIN code	10
	Joystick directions:	4x4 + 0x4
Op. time with cont. usage: 16 h	RF-power output:	10mW (by 50 ohm)
	Op. time with cont. usage:	16 h

The product picture above is for illustrative purposes only, actual product appearance might be slightly different