

## Auxiliary scaffolding 300 kg

8

Drive unit at top in head room Single entry or open through Auxiliary scaffolding 300 kg

**Dimension sheet** 





## **DATA SHEET**

Hinged doors at floor level Machine room at top of lift shaft With safety gear

1) This Data Sheet is for planning purposes only. An accurate layout drawing will be provided on receipt of an order. 뿐 DIN right DIN left Machine room access 품상품 (max. 12m) Distances between floors Push button designation 4 3 2 DW=CW= 200 200 Travel height=  $\bowtie$  $\bowtie$ SW= Machine room access DIN right DIN left All hinged doors drawn "DIN right"

All dimensions are in mm, and are subject to modification.

The shaft must be rectangular and perpendicular. Maximum admissible deviation from plumb is +20 mm -0 mm. All dimensions are minimum dimensions.

Q	V	BKG	Layou		Car dimensions							Headroom	Pit depth	
			drawing	g		CW=	CD=	1 1	CH=	ia.		HR min. at	PD=min.	
kg	m/s	Туре	no.			min.	min.		min.					
						max.	max.		max.					
	0,15	300.15/43F	5-64310-0003			600	800		1300					
300						1000	1000		2000			CH+1350	170	
			Part No.								Edition			
			5-60002-0255							08/2009				